



Tracer Electronics LLC
6981 Eastgate Blvd. - Lebanon, TN 37090
T - (615) 285-3952 / F - (615) 285-3970
sales@tracerelectronicsllc.com
www.tracerelectronicsllc.com


 **PERGAM TECHNICAL SERVICES**

We Invent to Prevent

NEW

Remote Detector

Methane



Laser Methane mini
Compact and Portable Methane Gas Detector

Laser Methane mini G



General


Items	Specification
Target Gas	Methane (CH ₄)
Detection limits	1 ~ 50,000 ppm
Accuracy of detection	± 10 %
Detection distance	1.6 ft ~ 98 ft
Dimensions	0.2 (W) x 0.5 (H)
Calibration	Self calibration
Structure	Splash & Dust proof
Alarm	Audible & Visual

Specification SA3C50A


Items	Specifications SA3C50A
Battery Life	Approx. 4.5 hours (at 77 °F, Display Level:5, Flashing Guide Light)
Operating temperature	14 °F ~ 122 °F
Weight	1.16 lb or less (including Ni-MH Battery Pack)
Guide Laser Light Color	GREEN (Class 3R: 5 mW or below)
Certificate	CE (R & TTE)
Application	Indoor & Outdoors under strong sunshine
Connection	Bluetooth & Internet Access (Android)
Area of use	Non-Explosion proof area



Interaction with Android mobile devices



- > Bluetooth communication
- > Realtime data display (measuring results)
- > GPS data tracking
- > Data storage for traceability
- > Ability to capture and store images
- > Email data transfer



Laser Methane mini

ation

ne-containing gases
28 ft using an optional reflect sheet)
ft
egrated reference cell
)



Specification SA3C32A

Items	Specifications SA3C32A
Battery Life	Approx. 6 hours (at 77 °F, Display Level:5)
Operating temperature	1.4 °F ~ 122 °F
Weight	1.32 lb or less (including Ni-MH Battery Pack)
Guide Laser Light Color	RED (Class 2 : 1 mW or below)
Certificate	CE (ATEX & EMC)
Application	Indoor Hazardous Areas
Connection	none
Area of use	Explosion proof required area

Features of the new Laser Methane mini

A new era in portable methane detection has arrived. Truly portable and handheld, the Laser Methane Detector (LMD) and Laser Methane mini (LMm) offers users the ability to detect methane remotely. What once was a time consuming and resource draining procedure can now be completed in a fraction of the time by utilizing the best in Tunable Diode Laser Absorption Spectroscopy (TDLAS).

Current methods such as FID, require users to be within arm's reach of a potential methane source, and to position the detector into the gas cloud, often requiring scaffolding or special access equipment to reach the area of interest. In stark contrast, the Laser Methane handhelds only need the emitted beam to pass through the gas cloud in order to detect methane. By simply pointing the laser beam towards a suspected leak, or along a survey line the handheld detector will monitor the level if methane is detected.

Principle of measurement

Laser Methane is based on utilization of laser absorption spectrophotometer of methane gas for gas measurement. The system detects natural gas leaks by emitting a Laser at particular wavelengths and analyzing the light reflected back from the ground to determine how much was absorbed by the methane in the natural gas. The measured gas volume is expressed by the methane column density (ppm-m): methane density (ppm) multiplied by the thickness (m)



Difficult to reach areas

Accumulated gas clouds in commercial and industrial facilities are commonplace. The Laser Methane mini allows for detection removing the need for ladders, scaffolding or aerial platforms.

Additional technology features

- > Can detect faster than conventional method (Detection speed 0.1 sec).
- > Remote Detection
- > By simply pointing the laser beam towards the suspected leak or along the survey line.
- > Can detect through the window. Measurement of room filled with methane from outside.
- > Only sensitive to methane. No false reports.

Typical applications include

- > Emergency response
- > Industrial and commercial property surveys
- > Gas processing plants
- > Landfill monitoring
- > Distribution pipeline surveys
- > Transmission pipeline surveys
- > Refinery surveys



*1 Minimum detectable sensitivity may depend on the reflector/reflecting object and detecting distance.

*2 Warning label

Please use this device to detect the target gases only. Gases other than the target gases cannot be detected by this device.